

Functions

- Reposition automatically
- Bi-direction passing
- The three gates always being at the closing state
- The gates turn 120° at a time
- Input Interface - Dry Contact Digital Signal
- Three passing modes for both in and out:
 - Free in & out (without locked)
 - Limited in & out (controlled by access control system)
 - Forbidden in & out (locked & without access control system)
- Optical Induction (intelligent)
 - The low energy motor drive moves the turnstile column to next home position. the revolving speed is adjustable, a slight manual speed up is possible. If no passage is completed, the release will be cancelled after an adjustable time.
- Two or more direction can be controlled and with an LED direction indicator
- Optional indication of inside or outside counter
- With interface of switch compatible with all the access controller

Technical Specification

Framework:

- Framework - 202 (default)/304/ 316 Grade Stainless Steel
- Shell size - 1630*1500*2000mm (Standard)
- Finish - Brushed surface (default)/ polishing surface/hot-galvanized

Electric:

- Machine center - Germanic technological motor
- Operation voltage - AC220V (50Hz)/AC (110-240) (60Hz), Main board voltage: DC 24V
- Interface - one standard port - RS 485
- Control Panel with alarm and sounds indication function (optional)
- Transit speed - 20-30 persons per minute
- Work environment - Indoor/Outdoor
- Temperature - -20°C to 60°C
- Emergency and Traffic Light function

The future of technology

Full Height Turnstiles



CPW-221C



CPW-221A



CPW-223A



The future of technology

Full Height Turnstiles



The future of technology

Full Height Turnstiles

